

Ultratherm Product data sheet



Overview

This technical data sheet is for average rooms fitted with a combination of the 12mm on main walls and the 8mm tile for window/ door reveals.

Ultratherm is an internal insulation system for solid walls. It allows walls to be insulated without costly alterations to skirting boards, windows, covings and radiators. Ultratherm typically reduces heat loss through 9" solid brick walls by 40%, creating a more comfortable living environment and reducing energy bills. Ultratherm meets Building Regulations for use where it is not functionally or technically possible to install thicker insulation systems.

Ultratherm is supplied in convenient flexible tiles that allow it to be installed around awkward shapes and curves. Once applied, Ultratherm is plastered to create a wall surface ready for decoration.

Quality control management system

Ultratherm is manufactured in the UK under an ISO 9001:2008 certified quality management system.

System components

System Components	Pack Size	Weight	Typical Coverage
12mm tile pack	10	7KG	5m ²
8mm reveal tile pack	5	1KG	1.15m ²
Insulated stop bead	1	-	2.5 linear meters
Angle bead	1	-	2.5 linear meters
10 litres of adhesive	1	10KG	10m ²
300ml Detail adhesive	1	0.4KG	0.3m ²



Thermal resistance

Thermal resistance testing in accordance with ISO 8302:1991 (BS EN 12664: 2001).

Ultratherm with a plaster skim finish has a thermal resistance of 0.307 m² K/W. Ultratherm wall adhesive provides additional thermal resistance of approximately 0.02 m² K/W. Thermal resistance can be increased further by applying greater thickness of plaster, applying backing plaster before the finish coat or by using different types of plaster.

Improvement in thermal resistance of a solid 9" brick wall achieved by installing Ultratherm	
Thermal resistance of Ultratherm with plaster skim	0.307 m ² K/W
Resistance of un-insulated 9" solid brick wall	0.476 m ² K/W
Resistance with Ultratherm (excluding adhesive)	0.783 m ² K/W
'U' value of un-insulated 9" solid brick wall	2.1 W/m ² K
'U' value of 9" solid brick wall with Ultratherm	1.2 W/m ² K
Typical % improvement in 'U' value	40.00%
Expected service life	Over 25 years

Fire resistance

Ultratherm has a 'Class 0' fire rating in accordance with Building Regulation Approved Document B.

Testing classification based on:

BS 476: Part 6 1989 + A1:2009 (Fire propagation)

BS 476: Part 7 (Surface spread of flame)

The polyurethane foam used in the manufacture of Ultratherm also meets the following British Standards:

BS 5852 Ignition source crib 7

BS 6853 Annex B.2 Toxic fume

BS 853 Smoke density (3 metre cube test).



Reduction in carbon emissions

Carbon emission savings in representative properties:

		Emission savings (kg CO ₂ e p.a.)	
Property Type	Bedrooms	Gas	Electricity
End Terrace House	2	626	1806
Semi-Detached House	3	530	1530
Detached House	4	1903	5493

Fuel	Emissions (kg CO ₂ e/kWh)
Electricity	0.58982
Gas	0.20435

Cost savings

Cost savings in representative properties:

		Fuel Cost Savings (£ p.a.)	
Property Type	Bedrooms	Gas	Electricity
End Terrace House	2	136	444
Semi-Detached House	3	115	376
Detached House	4	414	1350

Fuel	Costs (p/kWh)
Electricity	0.58982
Gas	0.20435



Effects of condensation and other building moisture

Ultrotherm is manufactured from a unique formulation of vapour-permeable polyurethane (PU) foam. Although Ultrotherm has a high resistance to damage from exposure to moisture it is not intended to be used as a waterproofing barrier.

Vapour barriers

Ultrotherm does not require the installation of a vapour barrier. Relative humidity and air vapour pressure should ideally be controlled inside the property through appropriate ventilation. Where additional ventilation is required an 'Ultrovent' should be installed. Under certain weather conditions, moisture in the fabric of a solid wall construction building may move towards internal surfaces (reverse condensation). A vapour-barrier may be problematic in such cases. Where a vapour barrier is required it should be installed on the surface of the insulated wall by applying vapour-barrier paint or a similar product.

Controlling reverse condensation

Where reverse condensation is identified as a potential problem, Ultrotherm external water repellent should be applied to the surface of the external brickwork. Applying Ultrotherm external water repellent can increase thermal resistance by a further 0.16 m² K/W depending on the pre-treatment moisture content of the wall structure.

Installation instructions

Full installation instructions are provided on or within the packaging of the main Ultrotherm components. A printed step-by-step installation guide is also available separately. A video guide to installation and electronic version of the step-by-step installation guide are available on the Ultrotherm website.

Types of plaster that can be applied to Ultrotherm

Thistle Board-finish plaster is most suitable for skim coat plastering. Thistle Multi-finish may also be used. Built-up layers of lightweight gypsum plasters can be applied before the skim coat if required. Thistle Hardwall plaster increases impact resistance.



Decoration

Ultratherm can be decorated with most paint types and wallpaper coverings once the plaster finish has dried. Manufacturer's instructions should be followed.

Maintenance

Ultratherm does not require any form of maintenance under normal conditions. Any damage can be repaired using components from the Ultratherm product range. Decorator's filler can be used to repair minor damage to the plaster finish.

Storage

Ultratherm products have a minimum shelf-life of 12 months. Ultratherm tiles should be stored flat and not in direct sunlight. Ultratherm adhesives should be stored in a cool, dry location and not be exposed to frost.

For more information call; 020 8539 4707