

Brochure

'Fountain' Drinking Water Purifier Brochure
(Models: MP1K and MP2K)



The 'Fountain' Water Filtration System is a complete under-the-sink filtration system. The filter provides an average usage life of 6 months.


The 'Fountain' incorporates the 'Pearl' high-performance six stage filter within a strong, durable, white plastic housing.

The "Pearl" is quite simply the most sophisticated ceramic candle filter used in water filtration today. UK scientists are world leaders in the field of water purification and the "Pearl" cartridge was developed in this country using the most advanced technology available.

The 'Fountain' System will effectively remove unwanted contaminants including Bacteria, Chemicals, Metals, unsavoury odours and tastes for the provision of safe, fresh, healthy cooking and drinking water.

Pearl 1000 Cartridge Filtration Capabilities

Bacteria	99.99%
Particles, Rust, Sediment	99.99%
Chlorine	100.00%
Trihalomethanes	90-99%
Lead, Aluminium, Copper, Cadmium, Mercury	92-99%
Pesticides and Herbicides	93-98%
Phenols	97.99%
Solvents	90-98%
Xeno Oestrogen	90%+
Hydrocarbons	90%+
Flourathene	90.00%



Why The 'Fountain' Ticks All the Right Boxes?

- ✓ **Good quality-** for high operational reliability
- ✓ **Inexpensive** saves money
- ✓ **Environmentally** - No more bottled water and no chemical additives in the purification process
- ✓ **Adaptable** can be connected in line or in parallel for use in high capacity systems for higher flow and special needs
- ✓ **Versatile** with option of connections to enable the unit to be used in different places
- ✓ **User friendly** no special tools required and no electrical power needed.



Housing Construction

The MP1 housing is made from high quality NSF listed FDA grade 100% polypropylene and has the option of 1/4" threaded or quick release speed-fit connections. The housing is designed to hold one 1/4" BSP threaded cartridges.

(See separate data sheet for cartridge specification)



Technical Information

Technical Data: Operating Conditions	'Fountain' MP1 Housing only	MP1/K 'Fountain' Complete system
Overall Width	90 mm	90 mm
Overall Height	305 mm	305 mm
Housing Connections	¼ threaded or 3/8 speedfit	3/8 speedfit
Min Operating Pressure	10 psi	10 psi
Max. Operating Pressure	72.5 psi	72.5 psi
Max. Working Temperature	60 °C	60 °C
Shipping Weight (kg approx)	10 kg	20 kg

For advice call 020 8539 4707